


**QRS DISCS**
**G M S DRY**
**KGS Swiflex® K1**
**1006**
**Backing**

Colour coded QRS.

**Recommended speed**

 Metal: 3500-4000rpm.  
 Resin: 3000-3500rpm.  
 Max. 45m/s.

**Application**

The latest generation of flexible diamond dry grinding and polishing discs, by the inventor of the original KGS Swiflex® dry grinding products. To grind and polish granite, terrazzo and concrete.

**Accessories**

Use a red KGS Swiflex® M back-up pad with mushroom QRS for each metal disc and the black KGS Swiflex® R back-up pads for resin discs.

**Properties**

 Grit 50-400                      Metal bond  
 Grit 800-10000                Resin bond

On some occasions you have the opportunity to skip coarser grits.

**KGS Swiflex® K1 ø100/15mm QRS**

COLOUR/GRIT	CODE
50	1023.0960010
60	1023.0960011
120	1023.0960012
200	1023.0960013
400	1023.0960014
800	3023.30091
1500	3023.30092
3000	3023.30093
10000	3023.30094

**KGS Swiflex® K1 ø115/15mm QRS**

COLOUR/GRIT	CODE
50	1023.0960410
60	1023.0960411
120	1023.0960412
200	1023.0960413
400	1023.0960414
800	3023.30241
1500	3023.30242
3000	3023.30243
10000	3023.30244

**KGS Swiflex® K1 ø125/15mm QRS**

COLOUR/GRIT	CODE
50	1023.0960510
60	1023.0960511
120	1023.0960512
200	1023.0960513
400	1023.0960514
800	3023.30248
1500	3023.30249
3000	3023.30250
10000	3023.30251


**Accessories**
**KGS Swiflex® back-up pads QRS-M M14**

ø mm	CODE
ø100	8851.00429
ø115	8851.00430
ø125	8851.10005


**KGS Swiflex® back-up pads QRS-R M14**

ø mm	CODE
ø100	8851.00427
ø115	8851.00428
ø125	8851.10013

